POWER TILLER Mai : JY 3-4 RY1



Warranty 37 (ears

















Light Weight Control for Heavy Duty Howing All Gears Are Made With High Standard



POHER TILLER Mai : JY 3-4 RV1



SPECIFICATIONS

Model 3 Gears 4 Shafts (2 Forwards 1 Reverse)

Engine Diesel Engine 12 -14 hp Pulley Dia. 7" (180 mm.)

Gear Ratio 2000 rpm.

Engine pulley 3.5" (89 mm.)

 Gear 1
 4.8 km./h

 Gear 2
 16.5 km./h

 Reverse Gear
 2.2 km./h

Break System

Pulley Break (External Break/Drum Break)

Gear Oil

Pulley Break (External Break/Drum Break)

Gear oil no.90 5.5-6.0liter(Power tiller gear box)

/ 0.7liter (Rotary gear box) 1.0liter (Chain housing)

Clutch Type By adjusting belt tension

DISTINCTIVE FEATURES

- 1. JY3-4 RV1 is suitable for Dry and Water fields.
- 2. JY3-4 RV1 is suitable for all kinds of Vegetables.
- 3. JY3-4 RV1 is for Plowing weeds.
- 4. Long and Short Handles are available for various kinds of property.
- 5. Rotary size 60/80/100 cm. are selective for each size of properties.
- 6. 6 cm Blades on rotary are arranged with threaded type so it helps spreading shoveling force efficiently and smoothly.
- 7. It is designed for high performance with max. plowing depth up to 18 cm. with 2-3 cm. soil dia. Approximately.
- 8. From the rotary design on front stand and wheel supporting, make it easy to change the wheel.
- 9. It can be run the rotary itself which is for hilly to be flat place.
- 10. End Cover of Rotary is designed to be a rake which can be adjusted the level.
- 11. Both Metal and rubber wheel can be used with JY3-4 RV1.
- 12. Engine stand is designed with Ridge level concern.

ACCESSOREIS







DISC PLOUGH



SKI



TRAILER

Manufactured by: S.T.I. INTERNATIONAL CO.,LTD. 402 Rama 3 Rd., Bangklo Bangkholaem Bangkok 10120 Tel. (+66)-2291-3726 (12 Lines) Fax: (+66)-291-1045 www.sti-inter.com









