POWER TILLER Mai : JY 4-7 RY1



Warranty Jears















Light Weight Control for Heavy Duty Howing All Gears Are Made With High Standard



POWER TILLER Mai : JY 4-7 RY1



SPECIFICATIONS

Model 4 Gears 7 Shafts (3 Forwards 1 Reverse)

Engine Diesel Engine 12 -14 hp Pulley Dia. 7" (180 mm.)

Gear Ratio 2000 rpm.

Engine pulley 3.5" (89 mm.)

Gear 1 2.52 km./h Gear 2 6.40 km./h Gear 3 13.45 km./h Reverse Gear 2.66 km./h

Break System
Gear Oil

Pulley Break (External Break/Drum Break)
Gear oil no.90 5.5-6.0liter(Power tiller gear box)
/ 0.7liter (Rotary gear box) 1.0liter (Chain housing)

Streering Control Clutch Force (Manual Control)

Clutch Type Dry Clutch

DISTINCTIVE FEATURES

- 1. JY4-7 RV1 is suitable for Dry and Water fields.
- 2. JY4-7 RV1 is suitable for all kinds of Vegetables.
- 3. JY4-7 RV1 is for Plowing weeds.
- 4. Long and Short Handles are available for various kinds of property.
- 5. Rotary size 60/80/100 cm. are selective for each size of properties.
- 6. 6 cm Blades on rotary are arranged with threaded type so it helps spreading shoveling force efficiently and smoothly.
- 7. It is designed for high performance with max. plowing depth up to 18 cm. with 2-3cm soil dia. Approximately.
- 8. From the rotary design on front stand and wheel supporting, make it easy to change the wheel.
- 9. It can be run the rotary itself which is for hilly to be flat place.
- 10. End Cover of Rotary is designed to be a rake which can be adjusted the level.
- 11. Both Metal and rubber wheel can be used with JY4-7 RV1.
- 12. Engine stand is designed with Ridge level concern.

ACCESSOREIS







DISC PLOUGH



SKI



TRAILER

S.T.I. INTERNATIONAL CO.,LTD. 402 Rama 3 Rd., Bangklo Bangkholaem Bangkok 10120 Tel. (+66)-2291-3726 (12 Lines) Fax: (+66)-291-1045 www.sti-inter.com

Manufactured by:











